11

face on one of the at least one of the implant-engaging members and the associated retainer and a receiving region defined in the other of the at least one of the implant-engaging members and the associated retainer for receiving the raised surface.

- 15. The orthopedic implant inserter of claim 9, wherein each retainer further comprises a latch that is pivotally attached to an end of the shaft of the retainer and removably engageable with another end of the shaft of the retainer in the retaining configuration.
- 16. The orthopedic implant inserter of claim 15, wherein each implant-engaging member is pivotal about the pivot axis of the aligned mounting bores and each latch includes an integral surface that engages and biases the respective implant-engaging member toward a selected pivotal position 15 when the latch is in the retaining configuration.
- 17. The orthopedic implant inserter of claim 9, wherein the first and second handles either move away from or toward each other depending on a direction that the knob is rotated.
- **18**. The orthopedic implant inserter of claim **9**, wherein the 20 opening in the second handle is threaded and interacts with a threaded portion of the shaft of the adjuster.

12

- 19. The orthopedic implant inserter of claim 9, wherein the opening in the first handle receives an end portion of the shaft of the adjuster.
- 20. The orthopedic implant inserter of claim 19, wherein the end portion of the shaft of the adjuster is held in place in the opening in the first handle using a pin extending through the opening of the first handle in a direction perpendicular to an orientation of the shaft of the adjuster.
- 21. The orthopedic implant inserter of claim 9, wherein the shaft of the adjuster extends in a direction generally perpendicular to the first and second handles.
- 22. The orthopedic implant inserter of claim 9, wherein the shaft of each retainer extends through the associated handle and implant-engaging member when the retainer is in the retaining configuration.
- 23. The orthopedic implant inserter of claim 9, wherein the pivoting of the first and second implant-engaging members on the respective first and second handles changes a distance between the first and second implant-engaging members in the first plane.

* * * * *